

Design Polymerics

DP 88

Spray Edge Coating (duct butter)

DP 88 is an aerosol spray edge coating or "duct butter" designed to quickly and conveniently coat the edges of insulation. DP 88 combines the advantages of quick drying aerosol adhesive with the tack free and flexible properties of sealants & liner adhesives.

Recommended Uses:

- Encapsulating cut edges, rips and tears in fiberglass insulation.
- May be used on internally lined ductwork and rigid fiberglass ductwork

Features and Benefits:

- Convenient / Easy Application
- Tack Free After Curing
- Quick Drying
- Encapsulates Cut/Damaged Fiberglass
- Flexible
- Durable
- No CFC's
- CARB Compliant

Directions For Use:

Surface Preparations: Surfaces should be clean, dry and free from dirt, oil and any foreign matter.

Application: Use in well ventilated area. Shake can vigorously until ball rattles and then for another 30 seconds before use. Hold spray can tip 3 to 8 inches from the surface to be sprayed, always at a 90 degree angle to the surface. Apply even coats, overlapping passes slightly to insure proper coverage. Keep can moving to avoid excessive build-up, puddling, or bubbles. Dries to touch in 3-5 minutes. Fully cured in 30 minutes, For best performance, use this product at temperatures above 50 degrees F.

Important: After use, invert can and spray until only gas comes out to clear valve and spray tip.

Clean Up: Mineral spirits.

Danger! Extremely Flammable.

Contents under pressure. Do not puncture or incinerate can, even when empty. Keep away from heat and flame. Do not spray near sparks, open flames, or other ignition sources. Store at temperatures below

120 degrees F in an area away from direct sunlight. Do not discard can in garbage compactor. Always point spray tip away from yourself and others. Avoid breathing vapors or contact with eyes and skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Technical Data:

Color: Black

Chemical Family: Synthetic Rubber

Application Temperature: 50 to 110 degrees F

Service Temperature: -0 to 200 degrees F

Flammability: Extremely Flammable

Dry Time: Dries to touch in 3 to 5 minutes. Fully cures in 30 minutes.

Coverage: Typical application will yield up to 400 linear feet on 1 inch duct liner per can

Packaging: 6 oz cans supplied, 12 cans per case.

Shelf Life: 1 Year

KEEP OUT OF REACH OF CHILDREN CONSULT MSDS BEFORE USING

Notice To Purchaser: No warranties, expressed or implied are made including merchantability and/or fitness for a particular purpose. Under no circumstances shall Design Polymerics be liable for any loss or damage arising from the purchase, use, or inability to use this product, or for any special, indirect, or consequential damages. The user may send a sample of the product to Design Polymerics for testing. If such a test proves a product defect, the user's sole and exclusive remedy is either reimbursement of the purchase price of the product or replacement of the product. No fabricator, installer, dealer, agent or employee of Design Polymerics has the authority to modify the obligations or limitations of this warranty. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state; therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation upon purchase of a product.

Distributed By:

Vac Systems International

1800 East Cliff Road, #11

Burnsville, MN 55337 USA

800-597-3955, 952-808-1616, 952-808-1584 (fax)

E-mail: info@vacsysint.com Web Site: www.vacsysint.com